

# DECLARATION OF PERFORMANCE

No.: ATS INSERT AERO PANORAMA 800

**1. Unique identification code of the product type:**

BUILT-IN CASSETTE ENERGY FIREPLACE AIR HEATER ATS INSERT AERO PANORAMA 800

**2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):**

ATS INSERT AERO PANORAMA 800

**3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:**

HEATING OF INDOOR SPACES

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):**

THERMIKI TSALIKIS  
HEATING EQUIPMENT MANUFACTURING  
END OF KAPETAN EVKLEIDI ST., ORAIOKASTRO  
THESSALONIKI  
Tel. 2310 684595 - FAX. 2310 684595  
www.thermiki.gr  
Email: info@thermiki.gr

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

-

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:**

SYSTEM 4

**7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:**

EN 13229:2001.

**8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:**

-

**9. Declared performance:**

| Essential Characteristics                          | Performance | Harmonised Technical Specification |
|--|-------------|------------------------------------|
| Nominal heat output                                | 13.96 kW    | EN 13229:2001.                     |
| Efficiency   | 79.26%      |                                    |
| Average CO concentration at 13% O <sub>2</sub>     | 0.1141%     |                                    |
| Minimum safety distance from combustible materials | 800 mm      |                                    |
| Average flue gas temperature                       | 231°C       |                                    |

**10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.**

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:

Signed for and on behalf of the manufacturer by:

.....

(name and title)

..... (Place and date of  
issue)

THE DRAFTER .....

(Signature & Company Stamp)