

DECLARATION OF PERFORMANCE

No. : ATS INSERT AERO CORNER 800 / 01

1. Unique identification code of the product type:	ENERGY FIREPLACE INSERT CASSETTE ATS INSERT AERO CORNER 800																
2. Type, batch or serial number or any other element allowing identification of the construction product, as required by Article 11(4):	ATS INSERT AERO CORNER 800																
3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:	HEATING OF INTERIOR SPACES																
4. Name, registered trade name or registered trade mark and contact address of the manufacturer, as required under Article 11(5):	THERMIKI TSALIKIS MANUFACTURING OF HEATING PRODUCTS END OF KAPETAN EVKLEIDI, ORAIOKASTRO THESSALONIKI Tel. 2310 684595 – FAX. 2310 684595 www.thermiki.gr Email: info@thermiki.gr																
5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):	–																
6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:	SYSTEM 4																
7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:	EN 13229:2001.																
8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:	–																
9. Declared performance:	<table border="1" style="width: 100%; border-collapse: collapse; text-align: center;"> <thead> <tr style="background-color: #d3d3d3;"> <th style="padding: 5px;">Essential characteristics</th> <th style="padding: 5px;">Performance</th> <th style="padding: 5px;">Harmonised technical specification</th> </tr> </thead> <tbody> <tr> <td style="padding: 5px;">Nominal heat output</td> <td style="padding: 5px;">13.73 kW</td> <td rowspan="5" style="padding: 5px; vertical-align: middle;">EN 13229:2001.</td> </tr> <tr> <td style="padding: 5px;">Efficiency</td> <td style="padding: 5px;">79.04 %</td> </tr> <tr> <td style="padding: 5px;">Average CO concentration at 13% O₂</td> <td style="padding: 5px;">0.1151 %</td> </tr> <tr> <td style="padding: 5px;">Minimum safety distance from combustible materials</td> <td style="padding: 5px;">800 mm</td> </tr> <tr> <td style="padding: 5px;">Average flue gas temperature</td> <td style="padding: 5px;">231 °C</td> </tr> </tbody> </table>			Essential characteristics	Performance	Harmonised technical specification	Nominal heat output	13.73 kW	EN 13229:2001.	Efficiency	79.04 %	Average CO concentration at 13% O ₂	0.1151 %	Minimum safety distance from combustible materials	800 mm	Average flue gas temperature	231 °C
Essential characteristics	Performance	Harmonised technical specification															
Nominal heat output	13.73 kW	EN 13229:2001.															
Efficiency	79.04 %																
Average CO concentration at 13% O ₂	0.1151 %																
Minimum safety distance from combustible materials	800 mm																
Average flue gas temperature	231 °C																

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4:

Signed for and on behalf of the manufacturer by:

.....
(name and position)

.....

THE DRAFTER

(place and date of issue)

.....

(signature & company stamp)